- Release 120V Firmware 01.11.01 Build 0049
- Release 120V Firmware 01.11.00 Build 0028
- Release 120V Firmware 01.09.00 Build 0009

Release 120V Firmware 01.11.01 Build 0049

If upgrading to this version, the user is required to first upgrade Conext Gateway with the latest firmware. Refer to the XW Pro Amended Firmware Upgrade Procedure.

- Released: 18 Aug 2021
- Summary of Changes
  - Improved performance on low battery voltage or low SoC conditions by always allowing reconnection to the grid when it returns.
  - Improved Voltage Ridethrough
  - Improved Transient Over Voltage detection and response time

Release 120V Firmware 01.11.00 Build 0028

If upgrading to this version, the user is required to first upgrade Conext Gateway with the latest firmware. Refer to the XW Pro Amended Firmware Upgrade Procedure.

- Released: 01 Mar 2021
- Summary of Changes
  - AC relay disconnect and reconnect levels are moved from grid codes to AC settings menu (advanced).
  - Improved synchronization and transitions of multi-unit systems to backup power.
  - Reduced inrush current during backup power to grid tie transition.
  - Simplified the firmware upgrade process by preserving the existing grid code.
  - ISO-NE SRD 2018 Grid Code Compliance
  - NYSEG IEEE 1547a-2014 Grid Code Compliance
- Bug Fixes
  - Resolved grid code application mismatches.

Release 120V Firmware 01.09.00 Build 0009

Firmware release for UL1741-SA17 and SA18 CSA Release.

Confidential – Property of Schneider Electric Solar Inc.
When printed, this document is uncontrolled. Check to verify that this is the current version.

Page 1 of 2

If upgrading to this version, the user is required to first upgrade Conext Gateway with the latest firmware. The user is also required to re-apply the correct Grid Code for their region using Gateway user interface after the firmware upgrade. Refer to the XW Pro Amended Firmware Upgrade Procedure.

- Released: 21 Aug 2020

- Summary of Changes
    - Generator Input (AC2) settings are configured by default to match the grid code selection.
    - Improved grid forming frequency recovery after generator disconnects.
    - Improved the time to start grid forming upon external contactor feedback.
    - Added Force Disconnect Pulse feature which allows the shutdown of AC Coupled inverters before reconnecting to the grid.
    - Enabled SoC Control mode with Battery Monitor
        - Change inverter states based on SoC level.
        - AC Coupling controls improvements using SoC level.

- Bug Fixes
    - Fix AC2 generator qualification issues.

Confidential – Property of Schneider Electric Solar Inc.
When printed, this document is uncontrolled. Check to verify that this is the current version.

Page 2 of 2